

GH 7

HYDROSTATIC ALL PURPOSE FLAIL

Technical Data

ENGINES: - HONDA **GX200** OHV, 196 cc, 5.5 HP, 4.1 Kw (@ 3600 r.p.m.) one-cylinder, petrol.

STARTER: recoil starter. **FUEL TANK:** 3,1 Litres.

GEARBOX: hydrostatic transmission.

TRACTION: 2 wheel-drive.

ALL-PURPOSE FLAIL TRANSMISSION: with helical gears in oil bath.

SPEED: continuously variable from 0 to max 6 km/h + reverse speed from 0 to max 3 km/h.

P.T.O: at 965 revolutions with clockwise rotation.

PARKING BRAKE: engaged by pedal.

HANDLEBARS: with height and side adjustment.

DRIVING WHEELS: Tractor wheels 16x6,50-8 / 4.00-8.

ALL-PURPOSE FLAIL WHEELS: puncture proof.

CUTTING SYSTEM: rotor with 16 pairs of Y-shaped blades and a front opening with tilting flaps.

CUTTING HEIGHT: continuously adjustable from 30 to 110 mm by means of a crank lever and lock

device.

CUTTING WIDTH: 68 cm.

ROTOR DIAMETER: 29,5 cm.

ROTOR SPEED: 2700 rpm.

ATTACHMENTS: cm 68 all purpose flail, 117 cm central cutter double blade bar, 100 cm orientable

and tilting sweeper, 60 cm snow thrower, snow chains for wheels.

WEIGHT:

150 kg (with all purpose flail)

75 kg (without attachment)

DIMENSIONS:

Length: 2000 mm

Width: 800 mm

Height: 970 mm



AGRIGARDEN MACHINES

Grillo S.p.A. - Via Cervese 1701 47521 Cesena (FC) - ITALY Tel +39.0547.633111 - Fax +39.0547.632011 email: grillo@grillospa.it - www.grillospa.it