

# HM600

## WIDE AREA MULCHING FLAIL MOWER

**JACOBSEN**



- **A TRUSTED MÜTHING® TRIPLE FLAIL CUT**
- **SUPERB MULCHING & GRASS CLIPPING DISTRIBUTION**
- **STRENGTH, COMFORT & VERSATILITY MEET FINESSE**

The HM600 has been built in collaboration with Müthing® to deliver a robust, reliable mower with the ability to tackle the toughest jobs, and the finesse to manoeuvre in tight spaces while providing a quality after-cut appearance.

From a clean, fine, rolled finish across sports pitches to routine cuts, the HM600 leaves an even spread of mulched clippings. It also tackles the irregular cuts, bringing the lesser maintained areas back under control. The HM600 can visit one work site with the versatility to do it all, the productivity to do it fast and the flail technology for superior presentation.

<b>CUT WIDTH</b> <b>126"</b> <small>(3.2M)</small>	<b>CUT HEIGHT</b> <b>1.2" - 2.8"</b> <small>(30MM - 70MM) 0.2" (5MM) INCREMENTS</small>	<b>CUTTING CAPACITY</b> <b>8.5 AC</b> <small>(3.46HA) / HR AT 7.5MPH (12KM/H)</small>
<b>FUEL CAPACITY</b> <b>20.4 GAL</b> <small>(77.1L)</small>	<b>MOWER ENGINE</b> <b>KUBOTA®</b> <b>65.2HP</b> <small>(48.6KW) TURBODIESEL</small>	<b>TRANSPORT SPEED</b> <b>15 MPH</b> <small>(25KPH)</small>



SINCERELY

*Take*

For information and support:  
[www.jacobsen.com](http://www.jacobsen.com) / +44 (0) 1473 270 000 / +1-888-438-3946



Actual operating power output may vary due to conditions of specific use.  
 Run time will vary based on conditions of specific use, accessories, and terrain.  
 NOTE: Specifications, while correct at time of printing, may change without notice.

© 2021 Textron Specialized Vehicles Inc.





# HM600

WIDE AREA MULCHING FLAIL MOWER



Tilt steering wheel  
with Q Amp steering

InCommand™  
control system

Electronic  
unit locks

Tilt Sensor  
Technology  
(TST)

4 point tie down

Foldable ROPS

Fully adjustable  
suspension seat

Maintenance-free  
rear axle

SureTrac™  
4WD

Wet parking brakes



3.2m Müthing® cutting width for longer grass



Superb mulching and grass clipping distribution



Applicable for fine finish turf and sports

## DECKS & CUTTING UNITS

CUTTING UNITS	Batwing mower with independent Müthing® mulching flail units. 1 out-front and 2 wing units.
NUMBER AND SIZE	1 x 63" (1.6m) front flail unit, 2 x 39" (1.0m) wing flails; 12.5" (300mm) working diameter
BLADE MATERIAL	M Type heavy duty carbide flails with shark fin shredding bar for optimum spread and mulching of clippings. High strength structural steel hood with replaceable wear plate. Spring steel projectile guards. Bolt-on carbide wear skids.
DECK LIFT & LOWER	Individual via fingertip operated joysticks
CUTTING UNIT CONTROLS	Fingertip operated joysticks for individual unit lift/lower; cross-cut position. Electronic transport locks.

## TRACTION, BRAKES & SPEED

TRACTION DRIVE	Hydrostatic, automatic on-demand cross-flow 4 wheel drive in forward and on demand in reverse
DECK DRIVE	Three dedicated cutter pumps to hydraulic motors with mechanical dual V belt final drive
HYDRAULIC SYSTEM	13.3 gal. (50.2L) capacity regulated with side by side cooler
SERVICE BRAKES	Dynamic braking through hydrostatic traction system
PARKING BRAKES	Zero-maintenance electro-hydraulic wet parking brakes
STEERING	Hydraulic power steering with adjustable tilt steering wheel
MOWING SPEED	10mph (16.4km/h) electronically adjustable

## WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	4,429lbs (2,009kg), 4,808lbs (2,181kg) with cab
LENGTH	148" (3.76m) front deck down
OVERALL HEIGHT	83" ROPS up; 67" ROPS and decks down; 87" with cab (2.11m ROPS up; 1.70m ROPS and decks down; 2.2m with cab)
WHEELBASE	65" (1.65m)
TRANSPORT WIDTH	83" (2.1m)
WORKING WIDTH	137" (3.5m) with Müthing® flail units down

## WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

## ACCESSORIES

■ Road light kit	■ Cab accessories - road light kit, Rear wiper kit
■ Canopy/sunshade	
■ Climate controlled cab	

