



Super Certes



With its unrivalled reputation for precision mowing, the Super Certes is ideal for golf greens, cricket squares and grass tennis courts. Its ten blade cutting cylinder delivers 142 cuts per metre ensuring an immaculate uniform finish.

Pneumatic transport wheels provide easy transportation between sites and a steel front roller offers accurate height of cut settings from 3 - 13 mm. Like the Marquis it is available with 51 cm or 61 cm mowing widths. To further enhance the quality of cut an optional Verti-Groom can be purchased.

QUICK SPECS

Power: 2.1 kW (2.8 HP) @ 2700 rpm

Cutting Width: 51 cm (20"), and 61 cm (24")

Drive System: Centrifugal clutch with heavy duty roller to chain

Special Features: 142 cuts per metre for superfine finish

Check us out!



www.ransomesjacobsen.com

Super Certes

SPECIFICATIONS

Engine	
Type	Honda GX 120 QX9, single cylinder, air cooled, 4 stroke OHV petrol
Power	2.1 kW (2.8 hp) @ 2700 rpm
Displacement	119 cc
Starting System	Recoil, rope type
Fuel Capacity	2.5 litres (0.55 gallon)
Transmission	
Drive Train	Centrifugal clutch
Traction and Cylinder drive	Heavy duty roller chain
Rear Drive Roller	2-piece, cast aluminium with bevel gear differential
Transport Wheels	Quick release, pneumatic 11 x 4
Controls	
Hand lever and cable operated rear roller drive clutch, hand throttle, cylinder drive lever, engine on/off switch . Isolated, height and angle adjustable handles	
Weight and Dimensions	
Transport Width	51: 86 cm (33.8") 61: 96 cm (37.8")
Height	95 cm (37.4")
Length	95 cm (37.4")
Weight (inc grass box)	51: 97 kg (213.8 lb) 61: 104 kg (229.3 lb)
Cutting	
Cutting Cylinder	10-blade, 127 mm (5") diameter
Width of Cut	51 cm (20") and 61 cm (24")
Height of Cut	3 mm to 13 mm (0.12" to 0.5")
Thin Bottom Blade	1.5 mm to 11.5 mm (0.06" to 0.45")
Height of Cut Adjustment	Tool operated micro adjusters
Cylinder to Bottom Blade	Tool adjustment
Front Roll	Full width, steel smooth 64 mm (2.5") diameter running on ball bearings
Grass Box	Moulded polyethylene
Performance	
Cutting Productivity	51: 1110 m ² /h (1330 sq yd/h) 61: 1660 m ² /h (1920 sq yd/h)
Clip Rate	142 cuts/m (43 cuts/ft)
Ground Pressure	51: 0.28 kg/cm ² (3.99 psi) 61: 0.32 kg/cm ² (4.55 psi)
Operator	
Operator Ear Noise Level	51 and 61: 89 dB(A) ± 1.92 LWA
Hand/Arm Vibration Level	51: 4.77 ± 1.3 m/s ² 61: 2.75 ± 0.0 m/s ²
Measured Sound Level	51 and 61: 95.5 dB(A) ± 1.92 LWA
Optional Equipment	
Brush and comb set, Verti-Groom kit and outrigger rolls	