ECLIPSE 360 HYBRID DIESEL/GAS ELECTRIC HYBRID REEL MOWER





- · JAKE'S TRUSTED HYBRID REEL MOWER
- GREATEST REEL SELECTION, CONFIGURED FOR FINE SPORTS TURF
- AUTOMATIC HILL HOLD PARKING BRAKE
- UNIQUE SWING OUT CENTER CUTTING UNIT FOR EASE OF SERVICE

The Eclipse 360 Hybrid cuts more than grass. With this diesel or gas electric hybrid reel mower, fuel consumption, noise and maintenance downtime are all reduced. The Eclipse 360 Hybrid is Jake's trusted hybrid reel mower, ensuring the highest quality cut available on your golf course or sports field.

FUEL CAPACITY **O**GAL (19L)

0.062" **0.438**" (1.6MM - 11.1MM)

GAS 10 HRS DIESEL 15 HRS



SINCERELY

For information and support: www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946







ECLIPSE 360 HYBRID

DIESEL/GAS ELECTRIC HYBRID REEL MOWER







asy access swing-out centre unit



Automatic Hill Hold Parking Brake



Programmable frequency of cut

| REELS & BLADES | | |
|---|---|---|
| NUMBER AND SIZE | 3 x 22" (55.88cm) reels; 5" (12.7cm) diameter | |
| BLADE MATERIAL | Hardened, high manganese carbon steel | |
| CUTTING UNIT LIFT | New Long Life linear actuator | |
| CUTTING FREQUENCY | 0.036" - 0.250" (0.91 mm - 6.35 mm) with 15 blade reel, electronically adjustable | |
| TRACTION, BRAKES & SPEED | | |
| TRACTION DRIVE | Front / 2WD - AC; 4.4HP (3.3kW) continuous (Optional 3WD - PM; 3.2HP (2.4kW)) | |
| REEL DRIVE | One brushless DC motor per reel; 1.3HP (0.97kW) continuous | |
| HYDRAULIC SYSTEM | No hydraulic oil | |
| SERVICE BRAKES | Dynamic regenerative braking system | |
| PARKING BRAKES | Automatic electro-magnetic multi-plate | |
| STEERING | Variable ratio Drive-by-wire steering with feedback control | |
| MOWING SPEED | 0 - 5.0mph (0 - 8.9kph); electronically adjustable max speed | |
| TRANSPORT SPEED | 0 - 9.0mph (0 - 14.5kph); electronically adjustable max speed | |
| WEIGHTS & DIMENSIONS | HYBRID CASOLINE | HYBRID DIESEL |
| WEIGHT (excluding fuel) | 1322lbs (599kg) with all fluids | 1362lbs (618kg) with all fluids |
| LENGTH | 101" (2.56m) with catchers | |
| OVERALL HEIGHT (including ROPS) | 79.3" (2.01m) | |
| WHEELBASE | -52" (1.32m) | |
| TRANSPORT WIDTH | 67.7" (1.72m) | |
| WORKING WIDTH | 67.7" (1.72m) | |
| WARRANTY | | |
| MOWER WARRANTY | 2 Ye | ars |
| CONTRACTOR SAMPLE STATE OF ACCUSED AND ACCUSED. | | CHARLES TO THE SAME PROPERTY OF THE BUILDING OF |

ACCESSORIES

- Turf Groomer: 22" (55.9 cm) width and 0.25" (6.3mm) or 0.50" (12.7mm) spacing
- Spiker
- lacksquare Powered rear roller cleaning brush
- High cut kit 15/16" 2.4 cm when used with 2 3/16") roller
- Premium seat grammar seat in grey vinyl with suspension base, adjustable brackets
- ROPS mounted LED light kit
- Dew whip holder
- Canopy / sunshade kit adjustable
- I TOW
- Traction tire assembly 18 x 9.5 x 8 (wheel and tire)
- Turf brushing groomer
- Bi-directional groomers and brushes 3WD kit

ROLLERS

- 22" (55.9 cm) Grooved assembly steel disk roller 2" (5.1 cm) dia.
- \blacksquare 22" (55.9 cm) Grooved segmented machined aluminum roller 2½" (5.7 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (light duty) 2" (5.1 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (heavy duty) 2" (5.1 cm) dia.
- 22" (55.9 cm) Grooved machined steel roller 2¾6" (5.6 cm) dia.
- 22" (55.9 cm) Grooved machined aluminum roller 2%" (5.6 cm) dia.

